

Nordic Chef tæki og búnaður til sölu á góðu verði

- Fastus styrkti Nordic Chef keppnina og ráðstefnuna sem haldin var í Hörpu 30. maí til 2. júní 2019.
- Fastus lagði til hágæða tæki og búnað frá Electrolux sem keppendur notuðu í Nordic Chef og Junior Chef keppnunum.
- Um er að ræða tæki og búnað sem er lítið sem ekkert notað, eingöngu í þessar 2 keppnir eina helgi og fæst á MJÖG góðu verði að keppninni lokinni. Um er að ræða góðan afslátt frá listaverði.

Hafið samband við sölufólk FASTUS í síma 580-3900 eða komið til okkar í síðumúla 16 þar sem hægt að að sjá tækin.

ATH, UM TAKMARKAÐ MAGN ER AÐ RÆÐA



ELEF268200	ELECTRIC COMBI OVEN 6 GN 1/1 B LW
------------	-----------------------------------

Model: AOS061EBA2

615,000.-

Convection-steamer with dedicated steam generator guarantees a continuous supply of fresh steam at all times.

air-o-flow: fresh air is blown into the oven from the outside, after it is pre-heated it is pulled through the bi-functional fan, guaranteeing cooking evenness. Humidity controlled through By-pass technology that guarantees the efficient use of the steam generator thus reducing water and energy consumption. Manual injection of water to add additional moisture in the cell.

air-o-clean: built-in cleaning system with four automatic pre-set cycles and one semi-automatic cleaning cycle.

Cooking cycles: steam (100 °C), low temperature steam (25-99 °C), overheated steam (101-130°C), hot air (25-300 °C), combi (25-250 °C), regeneration. 2-step cooking with the possibility to combine different cycles. Half power, half speed and pulse ventilation controls. Food probe for precise cooking.

Double-glass door with book-like opening maintains a cool external temperature and incorporates a drip pan to collect excess condensation avoiding wet floors. Halogen lighting in the cooking chamber. Side panels and interior in AISI 304 stainless steel.

Supplied with n.1 tray rack 1/1GN, 65mm pitch.

Code: 268200

Technical Features:

Dimensions (WxDxH mm): 898 x 915 x 808

El. Power (kW): 10,10

Power supply: 400 V - 3+N+J - 50/60

Net Weight (kg): 132

Volume (m3): 1,00

Gross Weight (kg) 151



ELEF922195	Standur undir 6/10sk ofna 89x76x80cm
------------	--------------------------------------

Model: STBAOSQ610

67,000.-

Technical Features:

Dimensions (WxDxH mm): 891 x 762 x 803

Net Weight (kg): 27

Volume (m3): 0,70

Gross Weight (kg) 35



ELEF371176	Induction eldavél 4 hellur 20 kW
	MM
	Model: E7INEH400P

920,000.-

ELECTRIC INDUCTION COOKING TOP HP 800 MM

6 mm thick glass ceramic cooking surface with 4 independently controlled 5 kW induction zones. Induction top surface with seamless transition between individual heating zones. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Code: 371176

Technical Features:

Dimensions (WxDxH mm): 800 x 730 x 250

El. Power (kW): 20,00

Power supply: 400 V - 3+N+J - 50/60

Net Weight (kg): 40

Volume (m3): 0,38

Gross Weight (kg) 60



ELEF371113	Standur opinn 80cm fyrir grilltæki
	Model: E7BANH0000

42,000.-

OPEN BASE 800 MM

Open base to store pots, pans, sheet pans etc. To be installed below 700XP top units in island type installations with operations from one side. Constructed in stainless steel with Scotch Brite finish. Delivered with 50 mm height adjustable feet.

Code: 371113



ELEF727335	Kælisrápur 670l -2/+10°C,DIG,S/S
	Model: RE471FN

210,000.-

1-DOOR REFRIG 670L -2/+10°C,DIG,S/S

Full door refrigerator with internal and external structure in 430 AISI stainless steel; external back panel in galvanized steel and bottom panel in anti-corrosive material. Digital control with cabinet temperature display and setting and manual activation of defrost cycle. Fully compliant HACCP digital controls include visible alarms. Optimized back to front forced air flow provides even temperature distribution and fast cooling in any conditions. Fitted with 75 mm-thick cyclopentane insulating foam. On-site reversible door features lock and door microswitch to switch off the fan when the door is opened. Hidden evaporator to guarantee higher storage capacity and less corrosion problems. Built-in refrigeration unit; ventilated operation; automatic defrost and evaporation of defrost water. For ambient temperatures up to 43 °C. CFC and HCFC free. R134a gas in refrigeration circuit.

Supplied with n. 3x2/1GN Rilsan coated grids and n. 3 sets of 2 stainless steel grid runners.

Code: 727335

Technical Features:

Dimensions (WxDxH mm): 710 x 837 x 2.050

El. Power (kW): 0,20

Power supply: 230 V - 1+N+J - 50

Net Weight (kg): 122



ELEF132726	Vinnuborð 160x70
	Model: TG1600PN
ELEF855147	Undirhilla 160cm
	Model: RI1600N

59,000.-

WORK TABLE 1600 MM

The 50mm high worktop in 304 AISI stainless steel, 1mm in thickness, has upturned edges and incorporates a layer of sound deadening, waterproof and fireproof material. Square section legs 40x40mm on 1" height-adjustable feet in 304 AISI stainless steel.

Code: 132726



ELEF132808	Vaskaborð 120cm m.2 vöskum 50x50
	Model: LG1225PN

106,000.-

SINK UNIT 2 BOWLS 1200

Made from 304 AISI stainless steel. The 50mm high worktop in 304 AISI stainless steel, 1mm in thickness, is sound-deadened and has an overflow rim and welded corners. Integral rear upstand, h=100mm, with 8mm radius. All-round apron. Square section legs 40x40mm on 1" height-adjustable feet (+/-20mm) N. 2 bowls mm500x500x300h with overflow pipe and 2" drain hole.

Code: 132808

Technical Features:

Dimensions (WxDxH mm): 1.200 x 700 x 1.000



ELEF855319	Blöndunartæki einföld WITH SPOUT 3/4" SINGLE HOLE
	Model: SHT1-3P

17,000.-

MIXER TAP WITH SPOUT 3/4" SINGLE HOLE

Code: 855319

Technical Features:

Dimensions (WxDxH mm): 600 x 326 x 700

Net Weight (kg): 3

Volume (m3): 0,01

Gross Weight (kg) 3





ELEF283002	Salamander opinn 65cm
	Model: SEA65

194,000.-

EL.SALAMANDER,OPEN 3-SIDES,ADJ.TOP,650MM

Constructed in AISI 304 stainless steel. Table top model. Top with 8mm heating element can be moved vertically; open sides.

Individually controlled heating zones. Temperature control with energy regulator. Easily removable chromed steel cooking grid and drip tray.

Code: 283002

Technical Features:

Dimensions (WxDxH mm): 650 x 450 x 465

El. Power (kW): 3,80

Power supply: 230 V - 1+N+J - 50/60

Net Weight (kg): 50

Volume (m3): 0,22

Gross Weight (kg) 50

ELEF600114	Lofttæmingarvél TABLE-TOP SEALING L=310MM
	Model: EVP31N

266,000.-

VACUUM PACKER TABLE-TOP SEALING L=300MM

Table top model. Constructed in 304 AISI stainless steel.

Domed transparent Plexiglas lid. Pressure chamber with rounded corners. Unit pre-arranged to be connected to an inert gas system.

Digital control panel for programming and storing of up to 10 operating programs (including the external vacuum one).

Basic display shows the selected program and related settings, including alarm messages if errors are detected by the electronic board. Electronic board detects electronic malfunctions, color and oil level as well as other failures in the vacuum packing process. Safety system protects the machine in case of sealing bar overheating. Adapter for vacuum packing in external containers (optional accessory). Sealing bar length 310mm.

Code: 600114

Technical Features:

Dimensions (WxDxH mm): 390 x 640 x 330

El. Power (kW): 0,70

Power supply: 230 V - 1+N+J - 50





ELEF726629	Hraðkælir/frystir 32/28kg 10 BN 1/1
	Model: RBF101

678,000.-

BLAST CHILLER/FREEZER 32/28KG 10GN1/1

For 10 GN1/1 or 600x400 mm trays. Load capacity: chilling 32 kg; freezing 28 kg (UK guidelines). External and internal top, front and side panels in 304 AISI stainless steel. Internal rounded corners and drain. Right hinged, reversible full door. Built-in refrigeration unit. Electronic control, 5 standard and 10 programmable cycles. Automatic detection of food probe insertion. Automatic and Manual defrost. Blast chilling real residual time estimation (A.R.T.E.). Turbo cooling function. Specific cycles for ice cream. Evaporator with antirust protection. Digital temperature and time display. HACCP and Service alarms with data logging. Operating air temperature: +90 -41°C. For ambient temperatures up to 32°C. Cyclopentane insulation (HCFC, CFC and HFC free). R404a refrigerant gas (HCFC and CFC free).

Code: 726629

Technical Features:

Dimensions (WxDxH mm): 760 x 760 x 1.640

El. Power (kW): 1,59

Power supply: 400 V - 3+N+J - 50

Net Weight (kg): 140

Volume (m3): 1,30

Gross Weight (kg) 160

ELEF504258	Uppþvottavél húdd 9,9kW HOOD TYPE,INSULATED,FILTER,DET.D,80R/H
	Model: EHT8IG

545,000.-

HOOD TYPE,INSULATED,FILTER,DET.D,80R/H

304 Stainless steel construction to include double skin insulated hood, external, front and side panels, wash tank, tank filter plus wash and rinse arms. Uses 2 liters of clean 84°C final rinse water per cycle. Rinse temperature and pressure guaranteed by AISI 304 built in atmospheric boiler and built in rinse booster pump. Washing performance is guaranteed by a powerful 0.8 kW wash pump and upper and lower stainless steel revolving washing spray arms. Unit to feature "WASH SAFE CONTROL" led light. Green light will indicate that all items washed have been properly rinsed. CLEAR BLUE filtering system removes majority of soil from the wash water. The unit shall include drain pump, detergent and rinse aid dispenser pumps and is equipped with flexible fill hoses. Convertible from straight to corner operation and delivered on height-adjustable feet.

Code: 504258

Technical Features:

Dimensions (WxDxH mm): 752 x 755 x 1.567

El. Power (kW): 9,90

Power supply: 400 V - 3+N+J - 50





ELEF865303	Purrkborð 120cm
	Model: BHHLU12

41,000.-

DW TABLE UNLOADING&LOAD.1200MM-HOOD TYP

For hood type dishwashers. Constructed in 304 AISI stainless steel. N.2 square 40x40mm tubular legs on height-adjustable feet. Basket direction: from right to left and from left to right.

Code: 865303

Technical Features:

Dimensions (WxDxH mm): 1.200 x 600 x 910

Net Weight (kg): 12

Volume (m3): 0,16

Gross Weight (kg) 16



ELEF865329	Vaskaborð 120 t.við ELEF uppþv.vél
	Model: PTSBHT12L

137,000.-

PREWASH TAB+BOWL+STRAINER L>R 1200MM-HT Code: 865329

Technical Features:

Dimensions (WxDxH mm): 1.200 x 745 x 1.170



ELEF855329	Blöndunartæki m.sveiflu og barka

41,000.-

MIXER TAP+SPRAY ARM+SPOUT-3/4" SING.HOLE

Code: 855329

Technical Features:

Dimensions (WxDxH mm): 240 x 740 x 90

Net Weight (kg): 5

Volume (m3): 0,02

Gross Weight (kg) 7